



- FLEXIBLE CONDUIT EXTENSION
- THREADED PREFABRICATED LEAD COUNTER FLASHING
- RIGID CONDUIT PENETRATION
- LEAD PIPE FLASHING - PRIME AND SET IN PLASTIC CEMENT
- CONT. SEALANT - TOOLED TO DRAIN
- TOP PLY SHEET
- REINFORCING SHEET
- BASE PLY SHEET
- OVERLAY BOARD
- EXISTING SBS MEMBRANE - CLEAN & PRIME TIE IN AREA, OR HEAT SURFACE AS REQUIRED TO EMBED/REMOVE GRANULES
- EXISTING INSULATION ASSEMBLY - REMOVE AT PENETRATION WITHOUT DAMAGING EXISTING VAPOR BARRIER
- EXISTING VAPOR BARRIER
- EXISTING THERMAL BARRIER OR CONCRETE
- EXISTING METAL DECK
- EXISTING FIREPROOFING
- INFILL INSULATION - SIZE AS REQUIRED TO RESULT IN FLUSH FINISH w/ TOP OF EXISTING ROOF
- VAPOR BARRIER TARGET PATCH
- VAPOR BARRIER - PROVIDE 2-PLY FIELD WRAP WITH OFFSET FINGERS - ADHERE TO EXISTING VAPOR BARRIER

FIREPROOFING - RESTORE WHERE MISSING AND WHERE REQUIRED

CHANNEL SUPPORT - REMOVE EXISTING FIREPROOFING AS REQUIRED TO SECURE DIRECTLY TO METAL DECK - FASTEN THROUGH UNDERSIDE OF DECK WITH TOGGLE BOLTS

PIPE STRAP - SECURE TO CHANNEL SUPPORT

0707 SBS FLASHING - ELECTRICAL CONDUIT
SCALE: 3" = 1'-0"