

OUTLET NOTATIONS:

<u>PREFERRED SYMBOL</u>	<u>DESCRIPTION</u>
"a"	SWITCHED OUTLET, "a" INDICATES SWITCH CONTROL.
"B"	PEDESTAL MOUNTED ON BENCH TOP.
"BF"	BELOW FLOOR
"C"	MOUNTED 6" ABOVE COUNTER OF 42" AFF - COORDINATE EXACT MOUNTING HEIGHT WITH ARCHITECTURAL DRAWINGS`
"CLG"	CEILING MOUNTED
"D"	DEDICATED DEVICE ON INDIVIDUAL BRANCH CIRCUIT
"E"	EMERGENCY
"EXIST"	EXISTING DEVICE/EQUIPMENT
"F"	FLUSH FLOOR BOX WITH FIRE/SMOKE RATED PENETRATION
"GFCI"	GROUND FAULT CIRCUIT INTERRUPTER, PERSONAL PROTECTION
"GFPE"	GROUND FAULT PROTECTION OF EQUIPMENT
"H"	HORIZONTALLY MOUNTED
"IG"	ISOLATED GROUND RECEPTACLE WITH SEPARATE GREEN GROUND CONDUCTOR TO ISOLATED GROUND BUS IN PANEL
"M"	MODULAR FURNITURE SERVICE - PROVIDE FLEXIBLE CONNECTION, COORDINATE EXACT LOCATION WITH FURNITURE PLANS
"PED"	PEDESTAL MOUNTED WITH TWO HOUR FIRE/SMOKE RATED PENETRATION
"PT"	POKE THRU WITH TWO HOUR FIRE/SMOKE RATED PENETRATION
"S"	SURFACE MOUNTED FLOOR BOX
"SP"	SURGE PROTECTION RECEPTACLE
"T"	TAMPER RESISTANT SAFETY RECEPTACLE
"TL"	TWIST-LOCK
"W"	WALL MOUNTED DEVICE AT 48" AFF UNLESS OTHERWISE INDICATED
"WP"	WEATHERPROOF RECEPTACLE WITH "NRTL" LISTED COVER PLATE FOR WET LOCATION WITH PLUG INSTALLED - MOUNTED 48" AFF UNLESS OTHERWISE INDICATED
"+XX"	DIMENSIONED HEIGHT